



# 北京东科联合技术有限公司

TEL :010-65919939 /010-65911669/010-65916639 FAX :0086-10-58693539

## Material Safety Data Sheet

### 1) Identification of the substance/preparation and the company:

Name of goods: FULLY REFINED PARAFFIN WAX  
MELTING POINT: 56-58 DEG. C, SEMI REFINED  
OIL CONTENT: 0.5 PCT MAX

Producer: BEIJING DONGKE UNITED TECHNOLOGIES CO.,LTD

Supplier: BEIJING DONGKE UNITED TECHNOLOGIES CO.,LTD

Address: ROOM 918, FLOOR 9, BUILDING 2, NO. 22 GUANGHUA ROAD  
CHAOYANG DIST. BEIJING, CHINA

Tel: 0086-10-58695969

### 2) Composition/information on ingredients:

Ingredients	CAS	%Weight in product
Paraffin waxes( Petroleum), Hydrotreated	8002-74-2	100

### 3) Hazard Identification:

#### Emergency Overview

**As part of good industrial and personal hygiene and safety procedure, avoid all unnecessary exposure to the chemical substance and ensure prompt removal from skin, eyes and clothing.**

Hazard identification:		none
Certical hazards to man and the environment	solid	none
	liquid	May cause burns
Short-term contact	solid	No hazards
	liquid	May cause burns
Eye contact	solid	No hazards
	liquid	The hot fluid may cause damage to the eyes
Skin contact	powder	May be irritating
	solid	No hazards
inhalation	liquid	The hot fluid may cause burns
	solid	No hazards
	Liquid )	Inhalation of paraffin wax vapours or
	Powder )	powder-particles may cause respiratory tract



# 北京东科联合技术有限公司

TEL :010-65919939 /010-65911669/010-65916639 FAX :0086-10-58693539

---

Ingestion	solid	irritation
	liquid	No hazards, see point 11 toxicology
		Because of the temperature may cause burns on contact with mouth/oesophagus/stomach

---

#### 4) First Aid measures:

Immediate measures:	solid	none
	liquid	Same action as in case of burn
Eye contact	liquid	Flush eyes with cold water. Seek medical attention
Skin contact	liquid	Immerse the area in water to assist cooling, apply sterile cover. Seek medical attention.
inhalation		Not applicable
Ingestion		May cause damage only in liquid (hot) state.
		Same action as in case of burns.
Advice to physician		See above

---

#### 5) Fire-fighting measures:

Suitable extinguishing media	CO <sub>2</sub> , foam, dry chemical powder, sand
Extinguishing media which must be used for safety reasons	Water
Special exposure hazards arising from the substance, its combustion products, resulting gases	Incomplete combustion produces fumes, flue gases, carbon monoxide
Special protective equipment	Breathing protection independent of the ambient air
Additional information	Apply cold water in order to cool containers and environment exposed to danger.

#### Special Information:

Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece operated in positive pressure mode.

#### 6) Accidental release measures:

Personal precautions	solid	Not applicable
	liquid	Avoid contact with hot liquid



# 北京东科联合技术有限公司

TEL :010-65919939 /010-65911669/010-65916639 FAX :0086-10-58693539

Environmental precautions	Solid ) Liquid )	Keep away from drains and surface water
Method of cleaning up	solid liquid	Not applicable Contain the product, allow to cool and remove mechanically
Additional Instructions	solid liquid	Not applicable Inform authorities in the case of leakage of large amounts

## 7) Handling and Storage:

### Handling

Instructions for safe handling	solid liquid	There are no special regulations Usual handling of solid transport goods Usual precautions for handling fluids. Consider common hygiene measures for handling chemical substances
Instructions for prevention of fire and explosion	solid liquid powder	None Prevent aerosol generation during pumping Danger (of explosion) adopt measures to prevent dust-explosion; (see point 9)

### Storage

Requirements for storage rooms and conditions	Slabs/ ) powder/ ) pastilles) Liquid	Store under cool, dry and light protected conditions Storage tanks have to be installed and managed according to official regulations
Information on storage concerning incompatible substances		Liquid material is not allowed to contain water at temperatures above 100 °C (delay in boiling)
Additional information		See point 10=stability and reactivity

## 8) Exposure controls/ Personal protection:

### Exposure limits

Ensure good ventilations when processing at elevated temperatures.

### Personal protection





# 北京东科联合技术有限公司

TEL :010-65919939 /010-65911669/010-65916639 FAX :0086-10-58693539

Respiratory protection	solid	none
	liquid	Works in well ventilated rooms
Hand protection	solid	None
	liquid	Wear rubber or leather gloves
Eye protection	solid	None
	liquid	Wear safety goggles
Body protection	solid	None
	liquid	Wear protective clothing

## 9) Physical Properties:

Physical state:	White waxy solid. Above the melting point, liquid.	
Color (Saybolt) Min	+30	ASTM D156
Odour	1	
Melting point:	56-58°C	ASTM D87
Oil content Wt%	0~1.5	ASTM D721
Needle Penetration 1/10mm (25°C)	15 Max	ASTM D1321
FDA	Passed	172.886 78.3710
Mechanical Impurity and Water	Negative	Observation
Acid and Alkali with Water solubility	Negative	SH/T0407

## 10) Stability and reactivity:

Condition to avoid	liquid	High temperature, open flames, other sources
Material to avoid	Solid/ ) Liquid )	Avoid contact with strong oxidizing agents
Hazardous decomposition		Carbon dioxide, carbon monoxide

## 11) Toxicological information:

<u>Toxicological information</u>	
Summary	There is no evidence for toxic effects to experimental animal of paraffin wax
<u>Carcinogenicity</u>	no evidence ---NTP Carcinogen---
Ingredient	Paraffin Wax (8002-74-2)



# 北京东科联合技术有限公司

TEL :010-65919939 /010-65911669/010-65916639 FAX :0086-10-58693539

---

Known	No
Anticipated	No
IARC Category	None

---

## 12) Ecological Information:

---

Environmental Fate:	No information found.
Environmental Toxicity:	No information found.

---

## 13) Disposal considerations:

Where possible, arrange for product to be recycled. Dispose of via an authorized/licensed waste disposal contractor in accordance with local regulations. Do not dispose of near ponds, ditches, down drains or onto soil. Dispose of product and container carefully and responsibly.

---

## 14) Transport Information:

Not classified as hazardous for transport in solid form.

---

## 15) Regulatory Information:

Not classified as hazardous for supply.

---

## 16) Other Information:

### Disclaimer:

\*\*\*\*\*

**BEIJING DONGKE UNITED TECHNOLOGIES CO.,LTD provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose.**

**BEIJING DONGKE UNITED TECHNOLOGIES CO.,LTD NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, BEIJING DONGKE UNITED TECHNOLOGIES CO.,LTD WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.**